



# RELAYS FAST® RELAYS

## GENERAL PURPOSE RELAY

- Dependable, low cost solution for air conditioning and heating switching.
- Insulating Material - Constructed of UL recognized Class B insulating material
- Temperature Range - -40° to 150° Fahrenheit




## SINGLE POLE FAN RELAYS- SIMILAR TO TYPE 84 FAN RELAYS

Fast PN	DESCRIPTION	CONTACT RATING 125/250 VAC
F87110290	SPST, 24 V COIL	8 FLA / 48 LRA @ 250 VAC
F87110291	SPST, 110 V/120 V COIL	
F87110292	SPST, 208/240 V COIL	
F87110293	SPDT, 24 V COIL	12 FLA / 60 LRA @ 125 VAC
F87110294	SPDT, 110/120 V COIL	18 AMPS Resistive @ 277 VAC
F87110295	SPDT, 208/240 V COILS	18AMP INRUSH

## TWO POLE FAN RELAYS

- Vending machines
- Appliances
- Safety control
- Fan control
- Heating
- Air conditioning and general purpose switching



Fast Part No.	DESCRIPTION	DESCRIPTION	TERMINALS
F87110340	Two-Pole Fan Relays	DPDT, 24 VAC COIL	POWER
F87110341	Two-Pole Fan Relays	DPDT, 110/120 VAC COIL	POWER
F87110342	Two-Pole Fan Relays	DPDT, 208/240 VAC COIL	POWER
F87110343	Two-Pole Fan Relays	DPDT, 24 VAC COIL	POWER
F87110346	Two-Pole Fan Relays	DPDT, 24 VAC COIL	PILOT






# RELAYS FAST® RELAYS

## HEAVY DUTY FAN RELAYS

Fast Part No.	DESCRIPTION	DESCRIPTION	CONTACT RATING 125/250 VAC
F87110380	HEAVY DUTY FAN RELAYS	1NO & 1NC, 24 VAC COIL	12 FLA / 60 LRA @ 125 VAC
F87110370	HEAVY DUTY FAN RELAYS	SPDT, 24 VAC COIL	8 FLA / 48 LRA @ 250 VAC
F87110360	HEAVY DUTY FAN RELAYS	SPST, 24 VAC COIL	18 AMPS Resistive @ 277 VAC

## FAN CONTROL CENTER RELAYS

- 40 VA transformer
- 24 volt secondary
- Fits standard 4" Junction box.
- Self-contained unit requires no additional closure.
- Unit imprinted with wiring diagram
- Resistive contact rating: 15a @ 277v
- Inductive contact rating:
- 3/4 h.p., 12a @ 120v; 3/4 h.p., 6a @ 240v
- Relay coil volts: 24



Fast PN	CONTACT ARRANGEMENT	TRANSFORMER PRIMARY	PLUG-IN RELAY
F87104010	DPDT	120/208/240	Semi-Enclosed
F87104012	SPNO/SPNC	120	Semi-Enclosed
F87104013	SPDT	120	Semi-Enclosed
F87104014	SPST	120	Semi-Enclosed
F87104015	SPDT	240	Semi-Enclosed
F87104020	SPDT	120	Semi-Enclosed

